



999.00 EUR  
incl. 19% VAT, plus [shipping](#)

- J4125 Gemini Lake !
- 1x COM !
- Triple Display !
- MiniITX !

- Intel® Gemini Lake J4125 2.0GHz Quad Core MCP Processor (10W, Turbo 2.7GHz)
- 1\* DDR4 2400MHz SO-DIMM up to 8GB
- 2\* Realtek® RTL8119I GbE, 1\* M.2 E-key support WIFI/BT
- 1\* SATAIII, 1\* M.2 M-key
- 1\* HDMI, 1\* eDP, 1\* LVDS
- 2\* RS232/485, 4\* RS232, 2\* USB3.0, 5\* USB2.0
- 12V DC-in
- Thin Mini ITX Form Factor (170 x 170 mm)

Model	– JLI1S-5L
Form Factor	– Mini-ITX (6.7-in * 6.7-in, 170 * 170mm)
Processor System	– Intel® Gemini Lake J4125 2.0GHz/QC Core MCP Processor (10W, Turbo 2.7GHz) – Intel J4125 SoC chipset – AMI 128Mb Flash ROM BIOS
Expansion Slot	– 1* M.2 E-key (2230, support WIFI/BT Module)
Memory	– 1* DDR4 2400MHz SDRAM SO-DIMM up to 8GB
Graphics	– Intel® 600 series Graphics, shared memory – 1* HDMI 1.4 (Max Resolution : 3840x2160@24Hz, Co-lay VGA) – 1* LVDS (Max Resolution : 2560x1600@60Hz, Co-lay eDP) – 1* eDP (Max Resolution : 3840x2160@60Hz) – Support Triple Displays
Ethernet	– 2* Realtek® RTL8119I GbE

Audio	<ul style="list-style-type: none"> <li>- Realtek HD audio</li> <li>- 3W speaker amplifier</li> </ul>
Storage	<ul style="list-style-type: none"> <li>- 1* SATAIII (6Gb/s)</li> <li>- 1* M.2 M-key (2242/2280, SATA or NVMe PCIe2)</li> </ul>
Rear I/O	<ul style="list-style-type: none"> <li>- 1* HDMI</li> <li>- 1* RS232</li> <li>- 2* RJ45</li> <li>- 2* USB3.0</li> <li>- 2* USB2.0</li> <li>- Line-out/MIC</li> <li>- 12V DC-in</li> </ul>
Internal Connector	<ul style="list-style-type: none"> <li>- 3* USB2.0</li> <li>- 2* RS232/485</li> <li>- 2* RS232</li> <li>- 1* SATAIII</li> <li>- 1* SATA power</li> <li>- 2* M.2 (1* M-key, 1* E-key)</li> <li>- 8bit GPIO (5V)</li> <li>- 1* AT mode</li> <li>- 1* I2C/SMBUS</li> <li>- 1* FP_Audio</li> <li>- 1* speaker</li> <li>- 1* CPU Fan (W/O Smart FAN)</li> </ul>
Watchdog Timer	<ul style="list-style-type: none"> <li>- From Super I/O to drag RESETCON#</li> <li>- 256 segments (10sec ~ 255min)</li> </ul>
Power	<p>12V DC-in, AT/ATX Supported</p> <ul style="list-style-type: none"> <li>- AT: Directly PWR on as Power input ready</li> <li>- ATX: Press Button to PWR on after Power input ready</li> </ul>
Compliance	<ul style="list-style-type: none"> <li>- CE, FCC, RoHS, REACH</li> </ul>
Temperature	<ul style="list-style-type: none"> <li>- Operating: 0°C ~ 60°C</li> <li>- Storage: -20°C ~ 70°C</li> <li>- Humidity: 10% ~ 90% RH @40°C (non-condensing)</li> </ul>
OS Support	<ul style="list-style-type: none"> <li>- Windows 10, Linux</li> </ul>